SEAMLESS ILLUMINATION

FEATURES AVAILABLE

- Daisy chaining
- High power factor ballast
- Multiple paint options


Designed to tuck beneath an overhead storage unit, Tazetta seamlessly blends in with your desktop. Built with a slim profile and available in a variety of paint options, Tazetta effortlessly matches any workspace aesthetics. It also provides superior illumination distribution with an energy-efficient, fluorescent lamp.

TAZETTA



TAZETTA







Environmental considerations:

 ELE high power factor (high performance) electronic ballast for increased efficiency.

FEATURES

 Allows for daisy chain linking up to five fixtures maximum.

SPECIFICATIONS

Lengths: 24", 36", 48", 60"

T5 fluorescent

Ballast: NPF
Color temperature: 3500K
Standard colors: see below

Materials: powder coated steel and plastic

Lens: prismatic
Reflector: UV stable silver

Switch: two-position black rocker; center

Cord: 9' black cord, 90° SW plug, exit center

Mounting: keyhole slots or spring bar mount

Certifications: ETL listed: compliant to UL 153 & CSA C22.2 No. 250.4;

UL 1598; TAA; BAA (varies per options selected)

Warranty: 3 years, excluding lamps

	Suggested Shelf Size	Actual Length	Wattage
24" fixture	30"–36"	23.3"	14
36" fixture	42"-48"	35.1"	21
48" fixture	54"–60"	46.9"	28
60" fixture	> 72"	58.7"	35

COLOR FINISH OPTIONS

NEUTRAL: DARK: Sand 074 Black 078 White 003 Charcoal 066

Soft White 061

METALLIC:

GRAY: Metallic Champagne 138 Silver Star 077 Metallic Charcoal 021

Metallic Silver 058

- Non-standard finish colors available for an extra charge. See the Products and Specifications Guide for a complete listing.
- When specifying metallic colors, note that the end caps will be a non-metallic accent color.

SPECIFYING NOTES

- The starter power and master control fixtures are supplied with a 9' 18-gauge power cord with a 90° SW rotation fused plug. Both cords exit from the center of the fixture.
- Cord and power switch location on 24" fixture is left of center.
- Cords are not field exchangeable.
- The starter power fixture is available with a 90°, SW rotation fused plug only.
- One cord manager is included with each fixture, two cord managers included with each daisy chain fixture.

- When specifying the daisy chain option, specify one power cord fixture and up to three jumper cord fixtures and one end fixture—maximum total of five fixtures.
- The end line jumper cord has one jumper cord with male plug to complete daisy chain run. Length of jumper cord must be specified.
- The daisy chain cord needs 3" of clearance from cord exit to wall for avoidance of cord damage.

TAZETTA

NOTE:

*A system mounting code must be specified for spring bar mount. Please call customer service at 800.544.4899 for details.

	DESCRIPTION	CODE	
Step 1: Select length	24" fixture	MT5 24	
	36" fixture	MT5 36	
	48" fixture	MT5 48	
	60" fixture	MT5 60	
Step 2: Select color	Standard color finish	+.3-digit color code	
	Non-standard color finish		
Step 3: Add options	3000K lamp	+.TRI30	
	4100K lamp	+.TRI41	
	High power factor electronic ballast	+.ELE	
	Left cord exit	+.LH	
	Right cord exit	+.RH	
	Hardwire	+.HW	
	Straight plughead	+.SP	
	Independent switch	+.DCP	
	Master control	+.MCDCP	
	45" jumper cord	+.DCJ45	
	56" jumper cord	+.DCJ56	
	76" jumper cord	+.DCJ76	
	24" end line jumper	+.DCE24	
	45" end line jumper	+.DCE45	
	56" end line jumper	+.DCE56	
	76" end line jumper	+.DCE76	
	Linear prismatic batwing lens	+.BW	
	Fused plug; SW rotation (Chicago city code)	+.CHC9SW	
Step 4: Select	Keyhole slots		
mounting	Spring bar mount*	+.system code	
	•		

OPTIONS	DESCRIPTION	CODE
Cord managers	horizontal cord manager	CM1
	qty. 2, 2" vertical cord managers	CM2
	12" vertical cord manager	CM3
	qty. 50, horizontal cord managers	CM4