



**SPECIFICATIONS**

<b>COLOR TEMPERATURE</b>	3500K
<b>COLOR RENDERING INDEX</b>	92 CRI
<b>LUMINOSITY</b>	311 lumens
<b>SYSTEM WATTAGE</b>	6W; 11W with USB base
<b>PEAK FOOTCANDLES</b>	99
<b>RATED LIFE</b>	> 50,000 hours
<b>USB PORT</b>	type-A connector, 5V, 1.2A
<b>DIMMING</b>	continuous from 100%-15% with last-state memory
<b>SENSOR</b>	optional; turns fixture off after 30 mins. of inactivity and back on after sensing movement
<b>AUTO SHUT-OFF</b>	after 10 hours (± 15 min.)
<b>POWER SUPPLY</b>	18W wall transformer with 9' cord; black
<b>CORD</b>	3' silver cord with quick connector
<b>MATERIALITY</b>	aluminum and plastic
<b>CERTIFICATIONS</b>	ETL listed: compliant to UL 153/8750 & CSA C22.2 No. 250.4; FCC Part 15 Class B; TAA; BAA
<b>WARRANTY</b>	10 years fixture; 5 years power supply

**DIMENSIONS**

	PRODUCT			CARTON			
	W	H	D	W	H	D	WT.
Single arm	6"	15.5"	17.9"	35"	9"	10"	8.3 lbs.
Double arm	6"	15.5"	18.6"	35"	9"	10"	8.6 lbs.

**MOUNTING**

- Freestanding base
- Surface mount
- Clamp mount
- Slat Wall mount
- Panel mount

**ORDERING NOTES**

- USB charging option only available with freestanding base
- All mounting options are fixed to the fixture arm as a theft-deterrent feature and are not interchangeable
- The clamp mount applies to surfaces 0.9"–1.875" thick.
- Surface mount requires a 2.125" diameter hole be drilled into the work surface. Surfaces can be 1.2" thick maximum.
- When specifying a slat wall or panel mount, the office furniture system must be identified. Please contact Inside Sales at 800.526.5658 to specify.

**SUSTAINABILITY**

- Made with fully-recyclable powder-coated aluminum and plastic
- Includes auto-shut off and dimming features
- Optional, energy-saving occupancy sensor
- May contribute to LEED points



**CALIFORNIA RESIDENTS:** The power cord used within this product may expose you to chemicals including Di(2-ethylhexyl) phthalate (DEHP), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).