
Power Hub



L/GHTCORP

ANGUS



Medium unit shown

FEATURES:

- Up to eight AC receptacles and two DC jacks
- · Allows for easy space reconfigurement
- Perfect for height-adjusting desks

DIMENSIONS:

	W	Н	D
Small	10.6"	2.3"	4"
Medium	12.2"	2.3"	5.6"
Large	12.2"	2.3"	7.6"

SPECFICATIONS:

AC RECEPTACLES	120V; 15A	
DC JACKS (IF APPLICABLE)	24V; up to 200W	
POWER CORD	6' or 10' PVC cord in black or white; straight grounded plug	
INTEGRATED CORD (OPTION)	6' or 10' PVC cord in black or white, or woven cord in 4 colors	
STRAIN RELIEF	straight; 90° also available	
MATERIALITY	powder coated aluminum	
CERTIFICATIONS	UL962A listed; UL1310 listed power supply; Canada C22.2 308-18; FCC CFR-47 Part 15 Class A; TAA; USB ports compliant to USB-IF BC 1.2	
WARRANTY	2 years	

SUSTAINABILITY NOTES:

 Made with fully-recyclable aluminum. Please contact your local county or municipality to determine your local recycling options.

MOUNTING:

Angus mounts below the work surface (under-mount).

FINISH:



RECEPTACLE COLOR:



ANGUS

CONFIGURATIONS:

Small features (8) AC receptacles - (4) in the front and (4) in the back.

Small with integrated Nik unit features (8) AC receptacles - (4) in the front and (4) in the back with (1) attached Nik unit.

Medium features (8) AC receptacles - (4) in the front and (4) in the back, and (2) DC jacks- 60W or 100W total.

Medium with integrated Nik unit features (8) AC receptacles - (4) in the front and (4) in the back, and (2) DC jacks- 60W or 100W total with (1) attached Nik unit.

Large features (8) AC receptacles - (4) in the front and (4) in the back, and (2) DC jacks- 120W or 200W total.

Large with integrated Nik unit features (8) AC receptacles - (4) in the front and (4) in the back, and (2) DC jacks- 120W or 200W total with (1) attached Nik unit.

SPECIFICATION NOTES:

- Each unit Includes two cord managers. Additonal cord managers are available for purchase.
- Tamper-resistant outlets are available as a special order.
 Please contact Inside Sales at 800.526.5658 for a lead time estimate.
- AC receptacles are available with a south orientation only (ground pin down).
- The maximum total number of AC receptacles available on any size Angus + Nik combination is eight.
- Straight strain relief is standard. A 90° angle is also available. Please contact Inside Sales at 800.526.5658 to specify.
- Not intended for interlinking. Plugging other power units or extension cords into the AC receptacles may violate your local electrical code.
- If specifying an integrated Nik unit, every AC receptacle included within the Nik unit removes an AC receptacle from the back of the Angus unit.
- If specifying a integrated Nik option, multiple power configurations of Nik are available. Please refer to the Nik product specs for more detail.
- If specifying a integrated Nik option, please note that insurface mounting is not available.
- The under-mount requires a surface of a minimum .75" thickness.
- Interconnect cords are available to connect LightCorp Revo, Voyage, Tino, and Reed Premier fixtures.