


L/GHTCORP





#### **FEATURES**:

- · Superior articulation
- · USB charging in base
- · 5-point, slide-control dimming

#### **DIMENSIONS:**

	W	Н	D
MACK	5.1"	16"	17"

# **SPECIFICATIONS:**

ENERGY CONSUMPTION	6.6 system watts			
NUMBER OF LEDS	24 fractional LEDs			
LIGHT OUTPUT	350 lumens			
LED RATED LIFESPAN	50,000 hours			
COLOR TEMPERATURE	4000K			
COLOR RENDERING INDEX	> 82			
BRIGHTNESS ADJUSTABILITY	100%-25%; 5-step			
USB CHARGE PORT	Type-A connector, 5V; 1A max			
POWER SUPPLY	12-watt wall transformer with 6' 2" black cord			
MATERIALITY	aluminum and plastic			
CERTIFICATIONS	ETL listed: compliant to UL 153 & CSA C22.2 No. 250.4; FCC/ICES Class B			
WARRANTY	1 year, excludes power supply			

# **SUSTAINABILITY NOTES:**

- Made with fully-recyclable aluminum and plastic. Please contact your local county or municipality to determine your local recycling options.
- Dimming included as an energy-saving feature
- Lower power consumption
- Mercury-free
- Potential LEED points. For more LEED information please visit https://new.usgbc.org/leed-v41

#### **MOUNTING:**

Mack is available with a freestanding base.

### FINISH:



L/GHTCORP

#### **PHOTOMETRIC DATA:**

Footcandle outputs measured at 14" from the work surface.

	18"	12"	6"	CL	6"	12"	18"
12"	7	15	25	-	26	15	8
6"	10	24	51	-	52	26	12
CL	12	30	69	100	72	33	14
6"	10	24	53	74	54	27	12
12"	8	15	27	34	28	16	9

### **SPECIFICATION NOTES:**

- The arm has a 17" reach from the front of the base to the fixture head.
- · Total weight of the fixture is 1.98 lbs.
- · This fixture is not field serviceable.