

L / G H T C O R P

# Reed Premier

*Under Shelf Light*





Reed Premier sets the standard for under-shelf lighting with exceptional performance, refined design, and intuitive control. Its daisy-chainable configuration connects multiple fixtures seamlessly, while integrated dimming lets users adjust light levels for any task. Engineered for precision and reliability, Reed Premier enhances visibility and comfort from technical labs to personal workstations.

#### Features:

- Choose from five interlinkable lengths: 17", 24", 31", 44" and 58"
- Available in anodized (silver) or black finishes
- High output option available in all five lengths
- Energy-saving features such as auto shut-off and dimming included; modular or integrated occupancy sensor available as an option.
- Automatic turn-off after 10 hours ( $\pm$  15 min.)
- Single touch on/off with continuous dimming from 100%-15% with last-state memory
- Made with fully-recyclable anodized aluminum and plastic
- Includes mounting hardware for metallic, wood, or laminate surfaces
- 10-year warranty on fixture, 5 years warranty on power supply

#### Specifications (standard output):

Color temperature: 3500K

Luminosity: 473-1942 lumens

Peak footcandles: 79-151

Color rendering index: 92+ CRI

Rated lifespan: >50,000 hours

Height: 0.5" Width: 2"

System wattage: 6.8-25.3 watts

Cord: 9' black 18W; 11' black 60W

#### Certifications:

- ETL listed: compliant to UL 153/8750 & CSA C22.2 No. 250.4; FCC Part 15 Class B; TAA; BAA; UL 2108 CSA C22.2 No. 9
- Modular sensor certified UL 153 portable luminaire accessory CSA C22.2 No. 250.4
- May contribute toward LEED credits