



SPECIFICATIONS

ENERGY CONSUMPTION	see chart below
NUMBER OF LEDS	see chart below
LIGHT OUTPUT	see chart below
LED RATED LIFESPAN	> 60,000 hours
COLOR TEMPERATURE	3500K
COLOR RENDERING INDEX	83
POWER SUPPLY	18W wall transformer with 9' cord
MATERIALITY	plastic
CERTIFICATIONS	ETL listed: compliant to UL 153/8750 & CSA C22.2 No. 250.4; FCC Part 15 Class B; TAA; BAA
WARRANTY	5 years

	# LEDS	LUMENS	WATTAGE	SYSTEM WATTAGE
12" fixture	12	324	5.0	5.1
22" fixture	24	639	9.0	9.8
32" fixture	36	951	12.0	14.1
42" fixture	48	1244	16.0	18.2

DIMENSIONS

	STANDARD & ADDER FIXTURES		
	L	H	D
12" fixture	11.1"	.71"	.85"
22" fixture	21.2"	.71"	.85"
32" fixture	31.2"	.71"	.85"
42" fixture	41.3"	.71"	.85"

SUSTAINABILITY

- Made with fully-recyclable plastic
- Lower power consumption
- Mercury-free LED
- May contribute to LEED points

ORDERING NOTES

- Each fixture includes one end cap to enclose the open end of the fixture, two mounting screws and two adhesive horizontal cord managers
- Mounting magnets and keyhole slots are integrated into the fixture for most mounting applications
- Maximum four modular segments connected per 18-watt power supply
- Individual adder does not include an end cap
- Individual adder units cannot be added to the 42" fixture
- White power supply and cord available upon request
- Do not interlink with any other fixture family
- Additional cord managers are available for purchase

CARTON DIMENSIONS

	L	H	D	WT.
12" fixture	17.1"	2.5"	4.5"	< 1 lb.
22" fixture	17.1"	2.5"	4.5"	< 1 lb.
32" fixture	17.1"	2.5"	4.5"	1 lb.
42" fixture	17.1"	2.5"	4.5"	1.1 lbs.

 **CALIFORNIA RESIDENTS:** The power cord used within this product may expose you to chemicals including Di(2-ethylhexyl) phthalate (DEHP), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.