



SPECIFICATIONS

ENERGY CONSUMPTION	see chart below
NUMBER OF LEDS	see chart below
LIGHT OUTPUT	see chart below
LED RATED LIFESPAN	> 50,000 hours
COLOR TEMPERATURE	3500K standard; 4000K available
COLOR RENDERING INDEX	92+
POWER SUPPLY	18W wall transformer with 9' cord; 60W wall transformer with 11' cord
MATERIALITY	anodized aluminum and plastic
CERTIFICATIONS	ETL listed: compliant to UL 153/8750 & CSA C22.2 No. 250.4; FCC Part 15 Class B; TAA; BAA; UL 2108 CSA C22.2 No. 9. Modular sensor certified UL 153 portable luminaire accessory CSA C22.2 No. 250.4
WARRANTY	10 years fixture; 5 years power supply

	# LEDS		LUMENS		WATTAGE		SYSTEM WATTAGE	
	SO	HO	SO	HO	SO	HO	SO	HO
17" fixture	24	47	473	736	5.8	9.5	6.8	10.2
24" fixture	36	70	721	1109	8.6	13.4	9.9	15.7
31" fixture	48	94	970	1438	11.3	17.3	13.1	19.8
44" fixture	72	141	1446	2073	16.8	25.5	19.1	28.1
58" fixture	96	188	1942	2755	22.2	33.1	25.3	38.3

DIMENSIONS

	STANDARD FIXTURE			FIXTURE WITH SENSOR		
	W	H	D	W	H	D
17" fixture	16.4"	.50"	2"	17.2"	.76"	2"
24" fixture	23.3"	.50"	2"	24.1"	.76"	2"
31" fixture	30.1"	.50"	2"	30.9"	.76"	2"
44" fixture	43.7"	.50"	2"	44.5"	.76"	2"
58" fixture	57.4"	.50"	2"	58.2"	.76"	2"

SUSTAINABILITY

- Made with fully-recyclable anodized aluminum and plastic
- Energy-saving features such as auto shut-off and dimming included; occupancy sensor available as an option
- Lower power consumption
- Mercury-free LED
- May contribute to LEED points

ORDERING NOTES

- If automatic shut-off feature is not desired, please specify by contacting Inside Sales at (800) 526-5658
- If a 4000K color temperature is desired, contact Inside Sales at (800) 526-5658 for lead time
- Mounts for wood/laminate or magnetic application and two adhesive cord managers are included with each fixture. Additional cord managers are available for purchase.
- If interlinking fixtures, refer to the Reed Premier Interlinking Guide for acceptable wattage combinations
- 8" and 30" interlinking cords are included with adder fixtures
- Allow 2" on each end for interlink or power supply plug connection
- A 60-watt power supply is required when interlinking
- Add-on sensor includes 1" end-to-end connector and adds 3" to the total fixture length
- If using a sensor with the fixture, only one sensor is required per string of interlinked fixtures

CARTON DIMENSIONS

	L	H	D	WT.
17" fixture	35"	2.5"	2.5"	1.1 lbs.
24" fixture	35"	2.5"	2.5"	1.3 lbs.
31" fixture	35"	2.5"	2.5"	1.4 lbs.
44" fixture	48.4"	2.5"	2.5"	2.8 lbs.
58" fixture	63"	2.5"	2.5"	3.5 lbs.

 **CALIFORNIA RESIDENTS:** The power cord used within this product may expose you to chemicals including Di(2-ethylhexyl) phthalate (DEHP), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.