



### SPECIFICATIONS

COLOR TEMPERATURE	2700K
COLOR RENDERING INDEX	90+ CRI
LUMINOSITY	2173 lumens
SYSTEM WATTAGE	30.2W / 55W with USB
RATED LIFE	> 50,000 hours
DIMMING	100%-10% continuous; with last state memory
AUTO SHUT-OFF	after 10 hours
USB PORTS (OPTION)	2A; available in surface mount only
POWER SUPPLY	60W inline transformer with 11' cord
MATERIALITY	aluminum, steel, and acrylic
CERTIFICATIONS	ETL listed, compliant to UL 153, CSA: C22.2 #250, CEC Title 20
WARRANTY	5-year fixture; 1-year power supply

### MOUNTING

- Freestanding base
- Surface mount
- Surface mount with USB

### DIMENSIONS

	PRODUCT			CARTON			
	W	H	D	W	H	D	WT.
19" freestanding	12"	19"	12"	28"	17"	16.3"	22 lbs.
19" surface mount	12"	21.6"	12"	28"	17"	16.3"	15.1 lbs.
26" freestanding	12"	26"	12"	35.5"	17"	16.3"	23 lbs.
26" surface mount	12"	28.6"	12"	35.5"	17"	16.3"	16.5 lbs.

### SUSTAINABILITY

- Made with fully-recyclable aluminum, steel, and acrylic
- Energy-saving features such as auto shut-off and dimming included
- Lower power consumption
- Mercury-free LED
- May contribute to LEED points



**CALIFORNIA RESIDENTS:** The power cord used within this product may expose you to chemicals including Di(2-ethylhexyl) phthalate (DEHP), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).