

SPECIFICATIONS

COLOR TEMPERATURE	3500K
COLOR RENDERING INDEX	92 CRI
LUMINOSITY	295 lumens
SYSTEM WATTAGE	6W; 11W with USB base
PEAK FOOTCANDLES	114
RATED LIFE	> 50,000 hours
DIMMING	continuous from 100%-15% with last-state memory
SENSOR	optional; turns fixture off after 30 mins. of inactivity and back on after sensing movement
AUTO SHUT-OFF	after 10 hours (± 15 min.)
POWER SUPPLY	18W wall transformer with 9' cord; 60W wall transformer with 11' cord
MATERIALITY	anodized aluminum and plastic
CERTIFICATIONS	ETL listed: compliant to UL 153/8750 & CSA C22.2 No. 250.4; FCC Part 15 Class B; TAA; BAA; UL 2108 CSA C22.2 No. 9. Modular sensor certified UL 153 portable luminaire accessory CSA C22.2 No. 250.4
WARRANTY	10 years fixture; 5 years power supply

MOUNTING

- Mounts for wood/laminate or magnetic application included


ORDERING NOTES

- If automatic shut-off feature is not desired, please specify by contacting Inside Sales at (800) 526-5658
- If a 4000K color temperature is desired, contact Inside Sales at (800) 526-5658 for lead time
- Two adhesive cord managers are included with each fixture. Additional cord managers are available for purchase.
- If interlinking fixtures, refer to the Reed Premier Interlinking Guide for acceptable wattage combinations
- 8" and 30" interlinking cords are included with adder fixtures
- Allow 2" on each end for interlink or power supply plug connection
- A 65-watt power supply is required when interlinking
- Add-on sensor includes 1" end-to-end connector and adds 3" to the total fixture length
- If using a sensor with the fixture, only one sensor is required per string of interlinked fixtures


SUSTAINABILITY

- Made with fully-recyclable anodized aluminum and plastic
- Energy-saving features such as auto shut-off and dimming included; occupancy sensor available as an option
- Lower power consumption
- Mercury-free LED
- May contribute to LEED points

	PEAK FOOT-CANDLES		LUMENS		WATTAGE		SYSTEM WATTAGE	
	SO	HO	SO	HO	SO	HO	SO	HO
17" fixture	79	132	473	736	5.8	9.5	6.8	10.2
24" fixture	106	171	721	1109	8.6	13.4	9.9	15.7
31" fixture	125	200	970	1438	11.3	17.3	13.1	19.8
44" fixture	141	232	1446	2073	16.8	25.5	19.1	28.1
58" fixture	151	240	1942	2755	22.2	33.1	25.3	38.3



CALIFORNIA RESIDENTS: The power cord used within this product may expose you to chemicals including Di(2-ethylhexyl) phthalate (DEHP), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.



DIMENSIONS

	STANDARD FIXTURE			FIXTURE WITH SENSOR			CARTON			
	W	H	D	W	H	D	W	H	D	WT.
17" fixture	16.4"	.50"	2"	17.2"	.76"	2"	35"	2.5"	2.5"	1.1 lbs.
24" fixture	23.3"	.50"	2"	24.1"	.76"	2"	35"	2.5"	2.5"	1.3 lbs.
31" fixture	30.1"	.50"	2"	30.9"	.76"	2"	35"	2.5"	2.5"	1.4 lbs.
44" fixture	43.7"	.50"	2"	44.5"	.76"	2"	48.4"	2.5"	2.5"	2.8 lbs.
58" fixture	57.4"	.50"	2"	58.2"	.76"	2"	63"	2.5"	2.5"	3.5 lbs.