



SPECIFICATIONS

COLOR TEMPERATURE	3500K
COLOR RENDERING INDEX	92 CRI
LUMINOSITY	295 lumens
SYSTEM WATTAGE	6W; 11W with USB base
PEAK FOOTCANDLES	114
RATED LIFE	> 50,000 hours
USB PORT	type-A connector, 5V, 1.2A
DIMMING	continuous from 100%-15% with last-state memory
SENSOR	optional; turns fixture off after 30 mins. of inactivity and back on after sensing movement
AUTO SHUT-OFF	after 10 hours (± 15 min.)
POWER SUPPLY	18W wall transformer with 9' cord; black
CORD	3' silver cord with quick connector
MATERIALITY	aluminum and plastic
CERTIFICATIONS	ETL listed: compliant to UL 153/8750 & CSA C22.2 No. 250.4; FCC Part 15 Class B; TAA; BAA
WARRANTY	10 years fixture; 5 years power supply

DIMENSIONS

	PRODUCT			CARTON			
	W	H	D	W	H	D	WT.
Single arm	6"	15.5"	14.4"	35"	9"	10"	8.3 lbs.
Double arm	6"	15.5"	17.7"	35"	9"	10"	8.6 lbs.

MOUNTING

- Freestanding base
- Surface mount
- Clamp mount
- Slat Wall mount
- Panel mount

ORDERING NOTES

- USB charging option only available with freestanding base
- All mounting options are fixed to the fixture arm as a theft-deterrent feature and are not interchangeable
- The clamp mount applies to surfaces 0.9"–1.875" thick.
- Surface mount requires a 2.125" diameter hole be drilled into the work surface. Surfaces can be 1.2" thick maximum.
- When specifying a slat wall or panel mount, the office furniture system must be identified. Please contact Inside Sales at 800.526.5658 to specify.

SUSTAINABILITY

- Made with fully-recyclable powder-coated aluminum and plastic
- Includes auto-shut off and dimming features
- Optional, energy-saving occupancy sensor
- May contribute to LEED points



CALIFORNIA RESIDENTS: The power cord used within this product may expose you to chemicals including Di(2-ethylhexyl) phthalate (DEHP), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.